

Appl. No.: 10/672,446  
TC/A.U.: 3765 Docket No.: G03-01  
Reply to Office Action of July 26, 2004

### LISTING OF CLAIMS

Please amend the claims as follows:

1. (Currently amended) A golf glove and a ball marker comprising:  
the golf glove comprising:  
fingers, a thumb, a back surface divided by an opening into a lateral portion adjacent the thumb and a medial portion,  
a closure assembly attached to the lateral portion and the medial portion,  
the closure assembly includes an inner surface and an outer surface when closed;  
and  
a ball marker holder comprising:  
a retaining wall extending around at least a substantial portion of the ball marker and a cutout section defined by the removal of part of the retaining wall,  
a base portion within the retaining wall, the base portion having a first aperture defined therein, [[and]]  
a magnet for magnetically holding the ball marker and the magnet of a size and shape configured to be received within the first aperture[[.]] and  
the first aperture having an edge section for receiving and securing the magnet such that the magnet is embedded within the holder and the bottom surface of the magnet is in contact with the glove,  
wherein the rigidity of the magnet does not restrict the movement of a golfer's hand, and the magnet cannot be accidentally dislodged and lost.
2. (Cancelled)
3. (Original) The golf glove and ball marker according to claim 1, wherein the base portion includes a second aperture being located proximate the cut out section.
4. (Original) The golf glove and ball marker according to claim 1, wherein the height of the retaining wall at the cutout section is approximately level with top surfaces of the base portion and the magnet.

Appl. No.: 10/672,446  
TC/A.U.: 3765 Docket No.: G03-01  
Reply to Office Action of July 26, 2004

5. (Original) The golf glove and ball marker according to claim 1, wherein the ball marker holder includes a wing extension integral with and substantially encircling the retaining wall.
6. (Original) The golf glove and ball marker according to claim 1, wherein the ball marker is made from a ferromagnetic material.
7. (Currently amended) An article of clothing and a ball marker comprising:  
the article of clothing having an inner and outer surface; and  
a ball marker holder comprising:  
a retaining wall extending around a substantial portion of the ball marker,  
a cutout section defined by the removal of part of the wall,  
a base portion within the retaining wall, the base portion having a first aperture defined therein,  
a magnet for magnetically holding the ball marker and dimensioned to be received within the first aperture, [[and]]  
the first aperture having an edge section around the perimeter for receiving and securing the magnet such that the magnet is embedded within the holder and the bottom surface of the magnet is in contact with the glove, and  
wherein the rigidity of the magnet does not restrict the movement of a golfer's hand, and the magnet cannot be accidentally dislodged and lost.  
a wing extension integral with and substantially encircling the retaining wall, the wing extension being coupled to the article of clothing between the outer surface and inner surface[.].  
wherein the rigidity of the magnet does not restrict the movement of a golfer's hand, and the magnet cannot be accidentally dislodged and lost.
8. (Cancelled)

Appl. No.: 10/672,446  
TC/A.U.: 3765 Docket No.: G03-01  
Reply to Office Action of July 26, 2004

9. (Currently amended) The article of clothing and ball marker according to claim [[6]] 7, wherein a second aperture is defined in the base portion and located proximate the cutout section.

10. A method of making a golf glove in combination with a golf ball marker holder, the method comprising of:

making a conventional golf glove having a glove closure assembly comprised of a flap having loop fastening fabric overlying an area of hook fastening fabric, the flap having outer and inner surfaces;

providing a magnet of a predetermined configuration;

providing a ball marker holder comprising of a generally circular retaining wall defining a perimeter, having an opening at one end and a base portion at the other end, a first aperture defined in the base portion, the first aperture having an edge section for receiving and securing the magnet such that the magnet is embedded within the holder and the bottom surface of the magnet is in contact with the glove, the holder having an integral wing extension encircling the retaining wall and a cut out section defined by a removed segment of the retaining wall;

~~providing a generally rectangular magnet of a configuration to fit within the first aperture of the base portion, the base portion having a chord to define a section of the base portion cut away to create a second aperture;~~

fixing the magnet into the first aperture of the base portion; and

covering the magnet and base portion with the ball marker.